



### Description:

Our USB3.0 Type-A to Type-B Active Optic Cable is suited for critical and versatile installations where distance is required. This supports USB3.0 superspeed device connectivity with up to 10Gbps of data transfer over a light weight, flexible and ultra-small bend radius (40mm) in a hybrid cable.

### Key Features:

- Supports USB3.0 - compatible and incompatible versions
- Supports USB2.0 and USB1.1 devices - compatible version only
- Supports all USB 3.0 device types: control, interrupt, bulk and isochronous at up to 10Gbps
- Operates with USB3.0 superspeed host controllers
- Support for Windows, Linux and iOS operating systems
- Plug and Play - no drivers or downloads required
- All cables are of CMP (Plenum-rated) jacket

### Technical Specifications:

<b>Cable Diameter:</b>	4.5mm
<b>Operating Temperature:</b>	32°F to 122°F (0°C to 50°C)
<b>Storage Temperature:</b>	-4°F to 140°F (-20°C to 60°C)
<b>Operating Humidity:</b>	10-80% non condensing
<b>Available in Lengths:</b>	15m and 30m
<b>Package Contents:</b>	1x MS-USBAB-M Cable - 15m or 30m
<b>Compatibility:</b>	
MS-USBAB-15-BC	USB 3.0 AM-BM AOC, (Compatible Version)
MS-USBAB-30	USB 3.0 AM-BM AOC, (Incompatible Version)