



### Description:

Our USB-C Active Optic Cable for Video is suited for critical and versatile installations where distance is required. This cable supports Gen 2 Superspeed connectivity with up to 21.6Gbps of video over a light weight, flexible hybrid cable with an ultra-small bend radius (40mm) for the distribution of 4K 60Hz 4:4:4 video from compatible USB-C source devices (must support DP-Alt mode).

### Key Features:

- Supports USB 3.1 Gen 2 - 21.6Gbps data rates to DP1.2 standard with DP Alt Mode.
- Supports a wide range of resolutions up to 4K@60Hz (colour space 4:4:4), 3D and Deep Colour
- Supports HDCP, EDID, CEC, and 3D signals
- 40mm bend radius (max)

### Technical Specifications:

<b>Connector dimensions:</b>	15 x 38 x 7.5mm
<b>Cable Diameter:</b>	4.5mm
<b>Package dimensions:</b>	200 x 200 x 65mm
<b>Package weight:</b>	0.9kg (15m); 1.2kg (30m)
<b>Master carton quantity:</b>	10
<b>Operating temperature:</b>	32°F to 122°F (0°C to 50°C)
<b>Storage temperature:</b>	-4°F to 140°F (-20°C to 60°C)
<b>Operating humidity:</b>	10-80% non condensing
<b>Available in lengths:</b>	15m and 30m