

# MS-4KCam

4K Ultra HD USB Camera

 **Solutions**



## Key Features:

- **Ultra 4K HD**  
Support 4K Ultra HD with super resolution up to 4K@30fps/25fps encoding output, and down compatible with 1080p,720p.
- **Lens**  
Wide angle up to 120°. At the same time, it supports EPTZ to make it more bigger and visible.
- **Low Light**  
Star-level ultra-high noise ratio of the new CMOS image sensor can effectively reduce the low noise in the case of image noise, while the application of 2D and 3D noise reduction algorithm, significantly reducing the image noise, even under low light conditions, still keep the picture Clean and clear, the image signal to noise ratio up to 55dB or more.
- **Autoframing**  
Support intelligent automatic framing function, can be changed with the seat order of the meeting room, the camera automatic transfer to obtain the best composition.
- **Built in Microphone**  
Built in microphone array, omnidirectional pickup, pickup distance up to 6 meters, noise suppressing algorithm with excellent sound.
- **Easy installation**  
Standard with a damped rotating shaft bracket, adapted to almost 100% of displays on the market, easy to install, stable and reliable

UK: +44 (0)115 824 0296

EU: +34 911 232 072

USA (Toll Free): +1 888 3458995

Israel: +972 3 7207710

[sales@m4sol.com](mailto:sales@m4sol.com)

 **Solutions**  
From ideas to reality.

### Technical Specifications:

Camera	
<b>Sensor</b>	1/2.5", CMOS, Effective Pixel: 8.29M
<b>Scanning Mode</b>	Progressive
<b>Lens Mount</b>	M12
<b>Lens 1</b>	Focus: f=3.5mm, FOV: 84°
<b>Lens 2(Default)</b>	Focus: f=2.8mm, FOV: 120°
<b>Autofocus</b>	Support(84°)
<b>Minimal Illumination</b>	0.5 Lux @ (F1.8, AGC ON)
<b>Shutter</b>	1/30s - 1/10000s
<b>White Balance</b>	Auto, Indoor, Outdoor, One Push, Manual
<b>Camera bracket</b>	bracket with damper
<b>Digital Noise Reduction</b>	2D,3D digital noise reduction
<b>Backlight Compensation</b>	Support
USB Features	
<b>Operate System</b>	"Windows® 7 (1080p and under only), Windows 8.1, Windows 10 or higher macOS™ 10.10 or higher. Google™ Chromebook™ Version 29.0.1547.70 or higher Linux"
<b>Hardware Requirement</b>	"2.4 GHz Intel® Core 2 Duo processor or higher, 2 GB RAM or more. USB 2.0 port (USB 3.0 required for 4K)"
<b>Color System / Compression</b>	H.264 / MJPEG/YUY2/NV12
<b>Video Format</b>	4k@30fps/25fps, 1080p@30fps/25fps, 720p@30fps/25fps, 960x540p@30fps/25fps, 640x360p@30fps/25fps etc
<b>USB Video Communication Protocol</b>	UVC 1.1
<b>UVC PTZ</b>	Support(EPTZ)
Input/Output Interface	
<b>USB Interface</b>	1xUSB 3.0: Type B, female
<b>HDMI Interface (Optional)</b>	1xHDMI: Version 1.4

## Technical Specifications:

General specification	
Input Voltage	5V (USB power supply)
Current Consumption	600mA(MAX)
Operating Temperature	-10°C - 40°C (14°F - 104°F)
Storage Temperature	-40°C - 60°C (-40°F - 140°F)
Power Consumption	3.0W(MAX)
Size	194mm x 34mm x 42mm (without bracket)
Net Weight	0.5KG
MTBF	30000h