

USB-C 3.1 Gen 2 AOC Cable for USB-C Video 15m / 30m



Description:

Our USB-C Active Optic Cable for Video is suited for critical and versatile installations where distance is required. This cable supports Gen 2 Superspeed connectivity with up to 21.6Gbps of video over a light weight, flexible hybrid cable with an ultra-small bend radius (40mm) for the distribution of 4K 60Hz 4:4:4 video from compatible USB-C source devices (must support DP-Alt mode).

Key Features:

- Supports USB 3.1 Gen 2 - 21.6Gbps data rates to DP1.2 standard with DP Alt Mode.
- Supports a wide range of resolutions up to 4K@60Hz (colour space 4:4:4), 3D and Deep Colour
- Supports HDCP, EDID, CEC, and 3D signals
- 40mm bend radius (max)

Technical Specifications:

Connector dimensions:	15 x 38 x 7.5mm
Cable Diameter:	4.5mm
Package dimensions:	200 x 200 x 65mm
Package weight:	0.9kg (15m); 1.2kg (30m)
Master carton quantity:	10
Operating temperature:	32°F to 122°F (0°C to 50°C)
Storage temperature:	-4°F to 140°F (-20°C to 60°C)
Operating humidity:	10-80% non condensing
Available in lengths:	15m and 30m (custom lengths available on request)

Ordering Information:

15m length	MS-USBCV-15-BC
30m length	MS-USBCV-30-BC

Custom lengths available on request