MS-IP18AG

4K 60FPS 4:2:0 KVM
over IP Transceiver



Description:

The MS-IP18AG is an HDMI2.0 (4K 60FPS 4:2:0) KVM over 1GbE network solution. The transceiver is PoE powered from the network switch. The product features USB, KVM pass-through IR, RS-232 and CEC pass-through.

The MS-IP18AG is an IP based AV & KVM solution which combines KVM extender with matrix switcher to distribute streams through 1G network. Applied H.264/265 codec breaks the constraints of network bandwidth and enables the deployment of large-scale projects.

Key Features:

- The distribution integrated architecture provides smooth and uninterrupted operation with high fault tolerance, as the failure of any encoding unit will not affect the whole system.
- Supports real-time decoding of H.265 or H.264, resolution from 800x600 to 4096x2160, backward compatible with H.264. H264 fixed data rate is adjustable, to the lowest 128kHz.
- Supports real-time video encoding of 4k@60fps signals with clear and smooth video quality.
- Single unit provides unlimited signal distribution.
- Provides real-time monitoring of device status and can send immediate alarm through management server in case of any failure.
- Supports dual-network hot backup.
- Can be powered by PoE and a DC power supply for power redundancy.
- Supports data transmission on USB 2.0 ports.

MS-IP18AG

4K 60FPS 4:2:0 KVM
over IP Transceiver

M Solutions

Technical Specifications:

Video ports	HDMI Input and HDMI Output (HDMI 2.0, 4K@60FPS, 8bit, YUV420)
Network ports	1G RJ45 x 1, 1G SPF x 1
USB ports	USB 2.0 x 4
Audio input ports	3-PIN Phoenix x 1 / HDMI x 1
Audio output ports	3-PIN Phoenix x 1 / HDMI x 1
IR/10 ports	2
Low current relay	1
RS232 / RS485	3-PIN Phoenix x 1
Power supply	PoE or 12V 2A
PoE protocol	802.3af
Working temperature	0°C~ 70°C
Encoding format	H.264/H.265
Media format	RTSP
Network protocol	TCP/IP, UDP, IGMP
Stream data rate	6M~500Mbps



M Solutions

USA (Toll Free): **+1 888 3458995,** Israel: **+972 3 7207710**
Email: **sales@m4sol.com,** Web: **m4sol.com**